


ATV MOWER XL, 150, WITH FLAP

35-VKMATV150HXL



Strongest ATV mower in the Nordic region

- **32 Heavy Duty hammer flails weighing 345 g each: Robust cast flails for grass and saplings**
- **Working width 150 cm**
- **Strong bogie clevis with two 19x7-8 wheels on each side**
- **Adjust the angle of operation with the turnbuckle under the tow bar**
- **Skids at the sides for stable, smooth operation**
- **Chain guard at the front to protect against ejected stones and clippings**
- **Openable rear flap**
- **25 hp V-twin motor with 764CC**
- **Electric start-up**
- **Wheel base width 219 cm**
- **Moveable tow bar, right hung and centrally hung mounting**
- **Laser screwed plate handles for longer durability**

Heavy duty – for those who demand that bit more

With Kellfri's Heavy Duty Flail Mower for ATVs, you will be able to take care of your overgrown terrain. Robust chassis and bogie means that it can cope with most situations. The bogie enables the machine to run smoothly and it is responsive in tough and uneven terrain. A roller with Heavy Duty hammer flails weighing 345 g each makes cutting long grass and even saplings an easy task with your ATV Flail Mower.

Robust chassis and bogie means that it can cope with most situations. The bogie enables the machine to run smoothly and it is responsive in tough and uneven terrain. A roller with Heavy Duty hammer flails weighing 345 g each makes cutting long grass and even saplings an easy task with your ATV Flail Mower.

Its weight of 405 kg provides an effective force to press down branches and vegetation, delivering an excellent cutting performance. In order to achieve maximum power transmission from the 25 hp V-twin engine to the roller, the flail mower has been equipped with 3 cog belts and a powerful belt tensioner.

The tow bar is adjustable in five steps, it can also be positioned centrally on the chassis, which is unique for the industry. The flail mower can therefore be operated on both sides of your ATV; in other words, it can be centrally mounted and also right-hung on the chassis.

Increase speed with a flail mower fitted with a flap

- Fitted with a flap at the back, which releases the grass to avoid excessive accumulation under the hood. You save on fuel and reduce wear on the belts, and you can also operate at a higher speed than an ATV flail mower without a flap. The grass is also spread more evenly.
- Deals with tougher vegetation where there may be ground obstacles such as tussocks and roots
- Used primarily for topping pastures, parks and road verges
- Stable construction

It is recommended to open the rear flap when cutting very rough terrain.

TECHNICAL DATA

Working width	1500 mm
Engine Power	23 hp
Wheels	4 pcs 19x7-8 Boggi
Cutting height	Max: 220 mm Min: 10 mm
Operating speed	6-12 km/h
Engine	25 hp V-twin-engine 764CC
L x W x H	1720 x 2190 x 1100
Flails	32 pcs. 77 mm/345 g
Weight	405 kg

ACCESSORIES

Extend your application with these practical accessories.

35-PDVKMATV

Sideshift adjustment tow bar

23-DH

Dolly manual